

MATERIAL SAFETY DATA SHEET



Date Issued: 09/09/2008
MSDS No: 79
Revision No: 1

A-A-713 #38901 Fluorescent Green Lacquer

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: A-A-713 #38901 Fluorescent Green Lacquer

PRODUCT CODE: 111551

ALTERNATE TRADE NAME(S): None Known

MANUFACTURER

TriCom Coatings, Inc.
2639 North 31st Avenue
Phoenix AZ 85009
Service Number: 602-243-3293

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300
CHEMTREC (International Transportation) :(202)483-7616

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: DANGER! Flammable liquid and vapor. May cause eye, skin and respiratory tract irritation. May cause asphyxiation, or brain, lung or other organ injury if inhaled, swallowed or absorbed by the skin.

POTENTIAL HEALTH EFFECTS

EYES: Liquid is severely irritating to the eyes. High vapor concentrations are also irritating.

SKIN: Liquid is moderately irritating to the skin. Prolonged or repeated contact can result in drying of the skin which may result in skin irritation and dermatitis (rash). Liquid may be absorbed through the skin.

INGESTION: Ingestion may cause headache, dizziness, fatigue, and central nervous system depression along with gastrointestinal disturbances.

INHALATION: Vapors may be irritating to the nose, throat, and respiratory tract. Exposure to high vapor concentrations may cause central nervous system (CNS) depression. Aspiration of liquid may cause pneumonitis, pulmonary edema, and hemorrhaging.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur.

MEDICAL CONDITIONS AGGRAVATED: Pre-existing eye and skin disorders may be aggravated by exposure.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Weight Percentage	CAS Number
Xylene*	31	1330-20-7
2-Butoxyethanol*	6	111-76-2
Methyl Amyl Ketone*	3	110-43-0
Acrylic Resin Solution	35	N/A
Proprietary Ingredients	25	N/A

* Toxic chemical subject to the reporting requirements of section 313 of Title III and of 40 CFR 372. "WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM."

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Seek medical aid if irritation persists.

SKIN: Flush skin with soap and water while removing contaminated clothing. If irritation occurs, seek immediate medical attention. Do not reuse clothing or shoes until thoroughly cleaned.

INGESTION: Do not induce vomiting, and seek immediate medical attention. Do not attempt to give any liquids if victim is unconscious.

INHALATION: Immediately remove victim to fresh air. If victim is not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

NOTES TO PHYSICIAN: If the victim is a child, give no more than 1 glass of water and 15cc (1 tablespoon) syrup of ipecac. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before emesis, gastric lavage should be considered following intubation with a cuffed endotracheal tube.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: <0° Fahrenheit, Tagliabue Closed Cup

FLAMMABLE LIMITS IN AIR BY VOLUME: 1.0% - 12.8%

AUTOIGNITION TEMPERATURE: No data available.

EXTINGUISHING MEDIA: Use water fog, "alcohol" foam, dry chemical, or CO₂.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

FIRE FIGHTING PROCEDURES: WARNING! Flammable Liquid. Clear the fire area of unprotected personnel. Do not enter confined fire space without full bunker gear; including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water. If water is used, fog nozzles are preferred

6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Keep material out of storm sewers and ditches which lead to waterways.

GENERAL PROCEDURES: WARNING. Flammable. Ventilate area of leak or spill for at least 24 hours or until it has been declared safe. Remove all sources of ignition. Stop the leak if there is no risk involved. Clean-up personnel require protective clothing and respiratory protection from vapors. Absorb liquid with inert material. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite liquid even in the absence of sparks or flame. Extinguish pilot lights, cigarettes, and turn off all other sources of ignition prior to use, and until all vapors are gone. Keep containers tightly closed and upright to prevent leakage.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ₃	ppm	mg/m ₃
Xylene	TWA	100	NL	100	NL
	STEL	NL	NL	NL	NL
2-Butoxyethanol	TWA	100	125	50	100
	STEL	NL	NL	NL	NL
Methyl Amyl Ketone	TWA	100	465	50	NL
	STEL	50	235	NL	NL

OSHA TABLE COMMENTS:

1. NL = Not Listed

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Section 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134, use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

COMMENTS: May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid / Gas

ODOR: Typical paint odor.

COLOR: Fluorescent Green

pH: N/A = Not Applicable

PERCENT VOLATILE BY VOLUME: 100.00%

VOLATILE ORGANIC COMPOUNDS: 3.64 LB/GL (436 G/L)
(VOC Theoretical – As Packaged)

VAPOR PRESSURE: 760 mmHg at (20°C)

VAPOR DENSITY: Heavier than Air

BOILING POINT: No data available

FREEZING POINT: No data available

MELTING POINT: No data available.

SOLUBILITY IN WATER: Soluble in most organic solvents. Not soluble in water.

EVAPORATION RATE: Slower than ether.

DENSITY (LBS/GALLON): 13.35

SPECIFIC GRAVITY: 1.60

MOLECULAR WEIGHT: N/A = Not applicable

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: Will not occur

POLYMERIZATION: Avoid heat, flame, and other sources of ignition.

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents. Prevent vapor accumulation.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

INCOMPATIBLE MATERIALS: Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

GENERAL COMMENTS: None identified.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Keep out of waterways.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: This material is a US EPA defined ignitable hazardous waste. The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION)**

PROPER SHIPPING NAME: Aerosols
PRIMARY HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKING GROUP: N/A
NAERG: 126
LABEL: Flammable Gas

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

311/312 HAZARD CATEGORIES: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

313 REPORTABLE INGREDIENTS: To the best of our knowledge, this product is not listed as a toxic chemical.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, this product is not listed as an extremely hazardous substance.

16. OTHER INFORMATION


REASON FOR ISSUE: New product.

PREPARED BY: Robert D. Commisso / President

REVISION SUMMARY: New MSDS

HMIS RATING

Health	2
Flammability	4
Reactivity	0
Personal Protection	H

NFPA CODES

ADDITIONAL MSDS INFORMATION: Last revision 10/17/2008.

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Griggs Paint of DomCom Enterprises, Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Griggs Paint assumes no responsibility for injuries from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

-----SECTION I-----

PRODUCT IDENTIFICATION

Griggs Paint
2639 North 31st Avenue
Phoenix, AZ 85009

EMERGENCY TELEPHONE NO.
 ChemTrec: 800-424-9300
INFORMATION TELEPHONE NO.
 602-243-3293

DATE OF PREPARATION
 September 9, 2008

Unfilled Omni-Pak[®] Cans Used With OMNI-FILL[®] Package OMNIFILL/ ISD

						<i>Enamel Blend</i>			<i>Lacquer, Acrylic, Vinyl</i>		
-----SECTION II-----		ACGIH	OSHA	Vapor	25106	25112	25116	25206	25212	25216	
CAS No.	HAZARDOUS INGREDIENT	TLV	PEL	Units	NMC EN-6	NMC EN-12	NMC EN-16	LAV-6	LAV-12	LAV-16	
(percent by weight)		<STEL>	<STEL>	(mm Hg)							
74-98-6	Propane (propellant)	1000	PPM	760.0	22	22	22	22	22	22	
75-28-5	2-Methylpropane(propellant)	Not Established		760.0	22	22	22				
67-64-1	§ Acetone	750	750	PPM	50	50	50	73	73	73	
		<1000>	<1000>								
763-69-9	Ethyl 3-Ethoxypropionate	Not Established		1.1	7	7	7	6	6	6	
NFPA Code 30B Level					3	3	3	3	3	3	
VOC as a percent by weight, BAAQMD Rule 49					100	100	100	100	100	100	
HMIS [®] Rating (Health - Flammability - Reactivity)					2-4-0	2-4-0	2-4-0	2-4-0	2-4-0	2-4-0	

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

111551

A-A-713 #38901 Fluorescent Green Lacquer

NOTE: *This MSDS covers unfilled OMNI-FILL[®] cans only. Users of filled cans must consult both this MSDS and the MSDS for the material filled into the can.*

Unfilled Omni-Pak® Cans Used With OMNI-FILL® Package OMNIFILL/ ISD

Section III – PHYSICAL DATA

PRODUCT WEIGHT - N.A.
SPECIFIC GRAVITY - N.A.
BOILING RANGE - <0-342 °F
VOLATILE VOLUME - 100 %

EVAPORATION RATE - Faster than Ether
VAPOR DENSITY - Heavier than Air
MELTING POINT - N.A.
SOLUBILITY IN WATER - N.A.

Section IV – FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION **FLASH POINT** <0 F PMCC **LEL** 1.0 **UEL** 12.8
RED LABEL – Extremely flammable, Flash below 21 °F
EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section V – HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mist.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITING. Give several glasses of water. Seek medical attention.

CHRONIC Health Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver and urinary systems.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section IV – REACTIVITY DATA

STABILITY - Stable

INCOMPATIBILITY

None known

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION - Will Not Occur

Section VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII – PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section II.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section IX – PRECAUTIONS

DOL STORAGE CATEGORY - 1A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Contents are EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated – Do not smoke – Extinguish all flames, pilot lights, and heaters – Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120 °F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.