

MATERIAL SAFETY DATA SHEET



Date Issued: 06/10/2009
MSDS No: 160
Revision No: 1

MIL-PRF-23377J Ty. 2 Cl. N Catalyst

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: MIL-PRF-23377J Ty. 2 Cl. N Catalyst

PRODUCT CODE: 200V34

ALTERNATE TRADE NAME(S): None Known

MANUFACTURER

TriCom Coatings, Inc.
2639 North 31st Avenue
Phoenix AZ 85009
Service Number: 602-243-3293

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300
CHEMTREC (International Transportation) :(202)483-7616

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: DANGER! Flammable liquid and vapor. May cause eye, skin and respiratory tract irritation. May cause asphyxiation, or brain, lung or other organ injury if inhaled, swallowed or absorbed by the skin.

POTENTIAL HEALTH EFFECTS

EYES: Liquid is severely irritating to the eyes. High vapor concentrations are also irritating.

SKIN: Liquid is moderately irritating to the skin. Prolonged or repeated contact can result in drying of the skin which may result in skin irritation and dermatitis (rash). Liquid may be absorbed through the skin.

INGESTION: Ingestion may cause headache, dizziness, fatigue, and central nervous system depression along with gastrointestinal disturbances.

INHALATION: Vapors may be irritating to the nose, throat, and respiratory tract. Exposure to high vapor concentrations may cause central nervous system (CNS) depression. Aspiration of liquid may cause pneumonitis, pulmonary edema, and hemorrhaging.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur.

MEDICAL CONDITIONS AGGRAVATED: Pre-existing eye and skin disorders may be aggravated by exposure.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | Weight Percentage | CAS Number |
|---|-------------------|------------|
| Methyl Ethyl Ketone* | 7 | 78-93-3 |
| N/ Butyl Alcohol* | 6 | 71-36-3 |
| Xylene* | 8 | 1330-20-7 |
| 2-Butoxyethanol* | 6 | 111-76-2 |
| Benzyl Alcohol | 5 | 100-51-6 |
| Propylene Glycol Monomethyl Ether Acetate | 5 | 108-65-6 |
| Resin Solids | 12 | N/A |
| Acetone | 15 | 67-64-1 |
| Benzyl Alcohol | 5 | 100-51-6 |
| Proprietary Ingredients | 31 | N/A |

* Toxic chemical subject to the reporting requirements of section 313 of Title III and of 40 CFR 372. "WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM."

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Seek medical aid if irritation persists.

SKIN: Flush skin with soap and water while removing contaminated clothing. If irritation occurs, seek immediate medical attention. Do not reuse clothing or shoes until thoroughly cleaned.

INGESTION: Do not induce vomiting, and seek immediate medical attention. Do not attempt to give any liquids if victim is unconscious.

INHALATION: Immediately remove victim to fresh air. If victim is not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

NOTES TO PHYSICIAN: If the victim is a child, give no more than 1 glass of water and 15cc (1 tablespoon) syrup of ipecac. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before emesis, gastric lavage should be considered following intubation with a cuffed endotracheal tube.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: 1° Fahrenheit, Tagliabue Closed Cup

FLAMMABLE LIMITS IN AIR BY VOLUME: 0.0% - 12.8%

AUTOIGNITION TEMPERATURE: No data available.

EXTINGUISHING MEDIA: Use water fog, "alcohol" foam, dry chemical, or CO₂.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

FIRE FIGHTING PROCEDURES: WARNING! Flammable Liquid. Clear the fire area of unprotected personnel. Do not enter confined fire space without full bunker gear; including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water. If water is used, fog nozzles are preferred

6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Keep material out of storm sewers and ditches which lead to waterways.

GENERAL PROCEDURES: WARNING. Flammable. Ventilate area of leak or spill for at least 24 hours or until it has been declared safe. Remove all sources of ignition. Stop the leak if there is no risk involved. Clean-up personnel require protective clothing and respiratory protection from vapors. Absorb liquid with inert material. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite liquid even in the absence of sparks or flame. Extinguish pilot lights, cigarettes, and turn off all other sources of ignition prior to use, and until all vapors are gone. Keep containers tightly closed and upright to prevent leakage.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:

| OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200) | | | | | |
|--|-------------|-----------------|-------------------------|------------------|-------------------------|
| EXPOSURE LIMITS | | | | | |
| | | OSHA PEL | | ACGIH TLV | |
| Chemical Name | | ppm | mg/m₃ | ppm | mg/m₃ |
| Methyl Ethyl Ketone | TWA | 200 | NL | 200 | NL |
| | STEL | NL | NL | NL | NL |
| N/ Butyl Alcohol | TWA | 150 | NL | 150 | NL |
| | STEL | 200 | NL | 200 | NL |
| Xylene | TWA | 100 | NL | 100 | NL |
| | STEL | NL | NL | NL | NL |
| Acetone | TWA | 750 | 1,800 | 750 | 1,780 |
| | STEL | 1000 | 2,400 | 1000 | 2,380 |
| Ethylene Glycol Monobutyl Ether | TWA | 100 | 125 | 50 | 100 |
| | STEL | NL | NL | NL | NL |

OSHA TABLE COMMENTS:

NL = Not Listed

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Section 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134, use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

COMMENTS: May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Typical paint odor.

COLOR: Amber, transparent liquid.

pH: N/A = Not Applicable

PERCENT VOLATILE BY VOLUME: 56.92%

VOLATILE ORGANIC COMPOUNDS: 3.04 LB/GL (364 G/L)
(VOC Theoretical – As Packaged)

VAPOR PRESSURE: 70.0 mmHg at (68°F)

VAPOR DENSITY: Heavier than Air

BOILING POINT: (133°F) to (401°F)

FREEZING POINT: No data available

MELTING POINT: No data available.

SOLUBILITY IN WATER: Soluble in most organic solvents. Not soluble in water.

EVAPORATION RATE: No data available

DENSITY (LBS/GALLON): 7.50

SPECIFIC GRAVITY: 0.90

MOLECULAR WEIGHT: N/A = Not applicable

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: Will not occur

POLYMERIZATION: Avoid heat, flame, and other sources of ignition.

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents.
Prevent vapor accumulation.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

INCOMPATIBLE MATERIALS: Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

GENERAL COMMENTS: None identified.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Keep out of waterways.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: This material is a US EPA defined ignitable hazardous waste. The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Paint

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN 1263

PACKING GROUP: II

NAERG: 128

LABEL: Flammable Liquid

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

313 REPORTABLE INGREDIENTS: To the best of our knowledge, this product is not listed as a toxic chemical.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, this product is not listed as an extremely hazardous substance.

16. OTHER INFORMATION

REASON FOR ISSUE: New product.


PREPARED BY: Robert D. Commisso / President

REVISION SUMMARY: New MSDS

HMIS RATING

| | |
|---------------------|---|
| Health | 2 |
| Flammability | 3 |
| Reactivity | 0 |
| Personal Protection | H |

NFPA CODES



ADDITIONAL MSDS INFORMATION: Last revision 06/18/2009.

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, TriCom Coatings, Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. TriCom Coatings, Inc. assumes no responsibility for injuries from the use of the product described herein.