



# TECHNICAL DATA SHEET

TECHNICAL DATA SHEET  
ELECTROSTATIC ALKYD PRIMER  
PAGE 1 OF 2

**PRODUCT:** A high quality, fast drying, low VOC alkyd enamel primer specifically formulated for electrostatic applications. This product is extremely durable with excellent flow and leveling characteristics.

**DESCRIPTION:** A specially formulated electrostatic industrial alkyd enamel primer. TriCom's Electrostatic Alkyd primers are durable, have extremely high rust/corrosion inhibitive properties, and are easy to apply.

**PROPERTIES:** COLORS..... White, Gray, Red Oxide  
SOLIDS(Weight)..... 59 - 71%  
SOLIDS(Volume)..... 49 - 50%  
THEORETICAL COVERAGE..... 300-350 sq.ft/gal\*  
**DRYING TIME-AT 75 DEGREES F:**  
TO HANDLE..... 30 Minutes  
TO RECOAT..... 1 Hour  
VEHICLE TYPE..... Modified Alkyd  
WEIGHT/GAL..... 12.2 - 12.8 lbs/gal  
\* Coverage @ 2 Mil Dry Film.

**ADVANTAGES:** (1). Great for Electrostatic Applications  
(2). Excellent Corrosion resistance  
(3). Extremely Durable.  
(4). Excellent Flow and Leveling.  
(5). Easy Application.



# TECHNICAL DATA SHEET

TECHNICAL DATA SHEET  
ELECTROSTATIC ALKYD PRIMER  
PAGE 2 OF 2

## **APPLICATION & REDUCTION:**

TriCom's Electrostatic Alkyd Primers are formulated specifically for electrostatic spray application. For spraying, thin up to 15%, or as needed with Xylene for proper flow and atomization specific to your spray equipment.

## **SURFACE PREPARATION:**

Surface must be clean, dry and free of all contamination before application.

## **PRECAUTIONS:**

Contents are COMBUSTIBLE.

Keep away from heat and open flame.

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.