



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
GLOSS POLYURETHANE VARNISH
(MPI #56)
Page 1 of 2

PRODUCT: A clear gloss polyurethane coating for use on interior and exterior wood.

DESCRIPTION: A polyurethane gloss coating formulated with special UV ray inhibitors for interior and exterior use. Ideal for use on doors, cabinets, wood trim, wood floors, boats, bartops, and furniture. It has excellent resistance to alcohols, oils, solvents, water, scuffing and abrasion.

PROPERTIES:

COLORS..... Clear
VOLATILE ORGANIC COMPOUNDS (VOC)..... 420 G/L Max
SOLIDS (weight).....45-46%
SOLIDS (volume).....36-38%
THEORETICAL COVERAGE.....565 sq.ft./gal.

DRYING TIMES:

SET-TO-TOUCH:..... Within 3 Hrs
DRY HARD:..... Within 6 Hrs

ADVANTAGES:

- (1). High Gloss Finish
- (2). Abrasion Resistant
- (3). Solvent and Chemical Resistant
- (4). Interior / exterior use
- (5). Smooth Uniform Finish
- (6). Excellent flow and leveling

USES:

- (1). Wood Cabinets
- (2). Wood Furniture
- (3). Wood Trim
- (4). Wood Floors
- (5). Wood Doors



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
GLOSS POLYURETHANE VARNISH
(MPI #56)
Page 2 of 2

APPLICATION:

TriCom's Hi-Gloss Polyurethane varnish is formulated for brush, roll, or spray application. For spraying and brushing, thin up to 1 pint per gallon with mineral spirits. Clean up with Mineral spirits or synthetic reducer.

SURFACE PREPARATION:

Surface must be clean, dry, and free of all contamination before application of varnish. Wood should be sanded with 180 grit sandpaper and wiped clean with a tac rag.

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN.

USE WITH ADEQUATE VENTILATION.

AVOID CONTACT WITH SKIN AND EYES.

READ MATERIAL SAFETY DATA SHEET BEFORE USING.

CONTENTS ARE FLAMMABLE.