



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
MIL-L-81352B TY. II
ALKYD ENAMEL
PAGE 1 of 2

PRODUCT: An exterior grade, alkyd based enamel formulated for low "VOC" content.

DESCRIPTION: A general purpose, exterior protective alkyd enamel coating for metal surfaces. This coating is particularly formulated for resistance to diester lubricating oil and heat for the aircraft industry. Available in gloss, semigloss and lusterless finishes.

PROPERTIES: COLORS..... Fed Std. 595B
VOC CONTENT.....340 G/L Maximum

ADVANTAGES: (1). Exterior Grade
(2). Single Component
(3). Low "VOC" Content
(4). Full Color Range, 595 Colors
(5). Fast Production Time.

USES: (1). Steel
(2). Machinery
(3). Tanks
(4). Wood
(5). Equipment
(6). Towers

SURFACE PREPARATION:

Surface must be properly prepared and primed, clean, dry, and free of all contamination before application.

APPLICATION & REDUCTION:

MIL-PRF-81352C Type II Alkyd Enamels can be applied by conventional or airless spray application. For spraying, thin up to 10% or as needed with MIL-T-81772B TY.3 Thinner. For brushing, reduce up to 10% with MIL-T-81772B TY.3 Thinner Brush small areas only.



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
MIL-L-81352B TY. II
ALKYD ENAMEL
PAGE 2 of 2

STEEL:

Surface must be clean and free of all oil, grease and foreign material. Badly rusted or pitted steel should be cleaned by commercial sandblasting and primed the same day.

PRECAUTIONS:

Contents are FLAMMABLE.

Keep away from heat and open flame.

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.