



TECHNICAL DATA SHEET

**TECHNICAL DATA SHEET
WALKWAY COMPOUND
NONSLIP MIL-W-5044C**

PRODUCT: A non-slip walkway coating with non-skid properties.

DESCRIPTION: **MIL-W-5044C WALKWAY COATING** is a single component nonslip walkway compound coating for use on walkways of exterior aircraft surfaces. Type II contains grit for added non-skid properties and is for brushing and rolling applications only.

PROPERTIES:

COLORS..... Per Fed.Std. 595B
TYPE I: Smooth - No Grit
TYPE II: Grit Added
FINISH..... Flat or Semigloss
Solids(Weight)..... 52 - 55%
DRYING TIMES:
TACK FREE..... 15 Minutes
RECOAT..... 30 Minutes
FULL HARDNESS..... 24 Hours

ADVANTAGES: (1). Non-Slip.
(2). Air Dry.
(3). Fast Dry.
(4). Durable.

USES: (1). Exterior Aircraft Walkways.
(2). Heavy Traffic Areas.
(3). Non-Slip Requirements.

APPLICATION: Apply by brush or roll methods. Thin with MIL-T-81772B Type III Reducer or TT-X-916 Xylene as needed to facilitate proper flow. Do not over brush Type II so that an even distribution of the grit is achieved.