



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
TT-P-1510
LATEX ENAMEL
PAGE 1 OF 2

PRODUCT: An acrylic latex exterior enamel with quick dry and good adhesion specifically to wood or other architectural substrates.

DESCRIPTION: An acrylic latex exterior enamel formulated to provide a uniform finish that dries quickly and adheres tightly. It forms a tough and durable film that is resistant to scuffing and abrasion. It is ideal for use in homes, apartments, schools, hospitals, offices and warehouses. Rinses easily from hands and tools with soap and water. For interior and exterior use.

PROPERTIES: COLORS..... Full Range
SOLIDS (Weight)..... 56 - 60%
SOLIDS (Volume)..... 38 - 41%
THEORETICAL COVERAGE..... 515 sq.ft/gal
DRYING TIME-AT 75 DEGREES F:
TO TOUCH..... 20 - 30 Minutes
TO RECOAT..... 2 - 3 Hours

ADVANTAGES: (1). Tough and Durable.
(2). Quick Drying.
(3). Water-Base.
(4). Cleans Easily.
(5). High Hiding.
(6). Meets TT-P-1510

USES: (1). Interior/Exterior
(2). Doors
(3). Wallboard
(4). Masonry
(5). Metal
(6). Trim



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
TT-P-1510
LATEX SEMIGLOSS ENAMEL
PAGE 2 OF 2

APPLICATION & REDUCTION:

TT-P-1510 Acrylic Latex Exterior Enamel can be applied by brush, roll or spray. Use at packaged consistency for brush and roll applications. Thin with up to 1 pint of water per gallon of paint for airless spray application.

SURFACE PREPARATION:

Surface must be clean and free of grease, oil, chalk, dust, and other contaminants. Loose or peeling paint must be removed by sanding, scraping, waterblast or sandblasting. All mildew must be removed before application. Remove by scrubbing with a solution made of 1 quart household bleach in 3 quarts of water. DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER MIXTURE. Scrub to remove any contaminants. Careful surface preparation is the key to a long lasting and successful job.

PRECAUTIONS:

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection. Read Material Safety Data Sheet before use of this product.

Keep from Freezing.