



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
HYDRO-ACRYLIC STAIN 300
Series
Page 1 of 2

PRODUCT: A waterbase methacrylic monomer penetrating stain designed to give excellent water repellency and penetration. All colors are semi-opaque.

DESCRIPTION: TriCom's Hydro-Acrylic methacrylic monomer stain is a water-repellent, semi-opaque penetrating coating that meets TT-P-19D and will provide years of protection and beauty to any concrete surface or structure. Due to its superior penetrating properties, it exhibits excellent adhesion to properly prepared substrates. This coating also provides excellent weather and UV resistance.

PROPERTIES:

<i>COLORS</i>	<i>Full</i>	<i>Range</i>
<i>FINISH</i>	<i>Low Sheen to Flat</i>	
<i>PIGMENT</i>	<i>Inorganic Oxides</i>	
<i>VEHICLE</i>	<i>Methacrylic Monomer Resin</i>	
<i>WEIGHT/GAL</i>	<i>8.7 - 9.7 lbs.</i>	
<i>SOLVENT</i>	<i>Water</i>	
<i>VISCOSITY</i>	<i>150-500</i>	<i>CPS</i>
<i>SOLIDS (Volume)</i>	<i>21%</i>	<i>min.</i>

Coverage at 2 mils. (20% loss)..150 sq. ft. gal

RESISTANCE TO:

OILS.....	Excellent
GREASE.....	Excellent
WATER.....	Excellent
WEATHER.....	Excellent

ADVANTAGES:

- (1). Highly Durable
- (2). Meets TT-P-19D
- (3). Oil and Water Resistant
- (4). Penetrating
- (5). Low V.O.C. Content
- (6). Ultraviolet Resistant



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
HYDRO-ACRYLIC STAIN 300
Series
Page 2 of 2

USES: (1). Concrete Structures (4). Carports
(2). Driveways (5). Walkways
(3). Garages

APPLICATION & REDUCTION: TriCom's Hydro-Acrylic methacrylic monomer stain can be brushed, rolled or sprayed. This product is normally ready for application as supplied. If thinning is necessary, use clean tap water. Do not apply when ambient or surface temperatures below 50 degrees Fahrenheit.

PRECAUTIONS:

Use with adequate ventilation.

Avoid contact with skin and eyes.

KEEP OUT OF THE REACH OF CHILDREN!

Do not take internally.

Avoid breathing vapor or mist.

Read Material Safety Data Sheet before using this product.