



# TECHNICAL DATA SHEET

TECHNICAL DATA SHEET  
INTERIOR OILBASE WOOD STAIN  
TT-S-711C  
(MPI #90)  
PAGE 1 OF 2

**PRODUCT:** An interior oilbase wood stain that protects and enhances the natural texture of fine wood.

**DESCRIPTION:** A Ready-to-use interior oilbase wood stain that will protect and beautify the texture of natural wood. TriCom'S interior oilbase wood stains contain a blend of oils that seal and stain wood. It may be applied with or without wiping for interior trim, doors, paneling, cabinets and woodwork. It is formulated for lower VOC requirements

**PROPERTIES:**

COLORS..... Full Range  
SOLIDS (weight)..... 54-56%  
SOLIDS (volume)..... 49-51%  
THEORETICAL COVERAGE.....350 sq.ft./gal.  
**DRYING TIME at 75 DEGREES FAHRENHEIT:**  
TO HANDLE..... 1 to 2 Hours  
RECOAT TIME..... 12 to 16 Hours  
VEHICLE TYPE..... Modified Oils  
WEIGHT/GALLON.....7.9-8.2 Lb. / Gal.

**ADVANTAGES:**

- (1). Seals and Stains
- (2). Beautifies Natural Grain of Wood
- (3). Meets TT-S-711C
- (4). Wipe or No-Wipe Application
- (5). Low Odor

**USES:**

- (1). Wood Cabinets
- (2). Wood Furniture
- (3). Wood Trim
- (4). Wood Paneling
- (5). Wood Doors



# TECHNICAL DATA SHEET

---

TECHNICAL DATA SHEET  
INTERIOR OILBASE WOOD STAIN  
TT-S-711C  
(MPI #90)  
PAGE 2 OF 2

**Application and Reduction:**

TriCom's Interior Oilbase stain may be applied by cloth, brush, spray or a combination of all three methods. Mix well before and during use to assure proper pigment suspension

**Surface Preparation:**

Surface must be clean, dry, and free of all contaminants. Wood should be prepared by sanding with 180 grit sandpaper and wiped with a tac rag.

**PRECAUTIONS:**

KEEP OUT OF REACH OF CHILDREN.

USE WITH ADEQUATE VENTILATION.

AVOID CONTACT WITH SKIN AND EYES.

READ MATERIAL SAFETY DATA SHEET BEFORE USING.

CONTENTS ARE COMBUSTIBLE.